


- $V_{CE}=650V$
- $I_C=60A@T_C=100$
- $V_{CE(sat)}=1.9V$

TO-247i

- Trench and field-stop technology.
- Easy parallel switching capability.

- High efficiency for inverters.
- High ruggedness performance.
- RoHS compliant.

- PFC applications
- Welding machines



Type	Marking	Package	Packaging Method
JJT60N65UK	T6065UK	TO-247i()	Tube



V_{CES}	Collector-emitter voltage	650	V
V_{GES}	Gate-emitter voltage	± 20	V
I_C	Continuous collector current ($T_C=25^\circ\text{C}$)	120	A
	Continuous collector current ($T_C=100^\circ\text{C}$)	60	A
I_{CM}	Pulsed collector current, t_p limited by T_{vjmax}	240	A
I_F	Diode continuous forward current ($T_C=100^\circ\text{C}$)	60	A
I_{FM}	Diode maximum current, t_p limited by T_{vjmax}	240	A
P_{tot}	Power dissipation ($T_C=25^\circ\text{C}$)	230	W
	Power dissipation ($T_C=100^\circ\text{C}$)	115	W
T_{vj}	Operating junction temperature range	-40 to +175	
T_{stg}	Storage temperature range	-55 to +150	

$R_{th(j-c)}$ Thermal resistance, junction to case for IGBT



BV_{CES}	Collector-emitter breakdown voltage	$V_{GE}=0V, I_C=250\text{ A}$	650	-	-	V
I_{CES}	Collector-emitter leakage current	$V_{CE}=650V, V_{GE}=0V$	-	-	50	A
I_{GES}	Gate leakage current, forward	$V_{GE}=20V, V_{CE}=0V$	-	-	100	nA
	Gate leakage current, reverse	$V_{GE}=-20V, V_{CE}=0V$	-	-	-100	nA
$V_{GE(th)}$	Gate-emitter threshold voltage	V				

D

0

9 11 ' 11



Switching characteristics

$t_{d(on)}$	Turn-on delay time	$V_{CC}=400V$ $V_{GE}=0/15V$ $I_C=60A$ $R_G=10\Omega$ Inductive load	-	44	-	ns
t_r	Rise time		-	100	-	ns
$t_{d(off)}$	Turn-off delay time		-	166	-	ns
t_f	Fall time		-	75	-	ns
E_{on}	Turn-on energy		-	2.3	-	mJ
E_{off}	Turn-off energy		-	1.3	-	mJ
E_{ts}	Total switching energy		-	3.6	-	mJ
$t_{d(on)}$	Turn-on delay time	$V_{CC}=400V$ $V_{GE}=0/15V$ $I_C=60A$ $R_G=10\Omega$ Inductive load $T_{vj}=175$	-	45	-	ns
t_r	Rise time		-	105	-	ns
$t_{d(off)}$	Turn-off delay time		-	180	-	ns
t_f	Fall time		-	76	-	ns
E_{on}	Turn-on energy		-	3.6	-	mJ
E_{off}	Turn-off energy		-	1.6	-	mJ
E_{ts}	Total switching energy		-	5.2	-	mJ



($T_{vj}=25$ unless otherwise specified)

V_F	Diode forward voltage	$I_F=60A$	-	2.5	-	V
		$I_F=60A, T_{vj}=175$	-	2.0	-	V
t_{rr}	Diode reverse recovery time	$V_R=400V$ $I_F=60A$ $di_F/dt=-450A/s$	-	78	-	ns
I_{rrm}	Diode peak reverse recovery current		-	15	-	A
Q_{rr}	Diode reverse recovery charge		-	511	-	nC
t_{rr}	Diode reverse recovery time	$V_R=400V$ $I_F=60A$ $di_F/dt=-450A/s$ $T_{vj}=175$	-	126	-	ns
I_{rrm}	Diode peak reverse recovery current		-	26	-	A
Q_{rr}	Diode reverse recovery charge		-	2163	-	nC




Fig 1. Typical output characteristic ($T_{vj}=25^{\circ}\text{C}$)




Fig 2. Typical output characteristic ($T_{vj}=175^{\circ}\text{C}$)




Fig 3. Power dissipation as a function of T_c




Fig 4. Typical Gate charge




Fig 5. Typical $V_{GE(th)}$ as a function of T_{vj}
($I_C=1\text{mA}$)




Fig 6. Typical V_F as a function of T_{vj}




Fig 7. Typical V_{CEsat} as a function of T_{vj}




Fig 8. Typical I_F as a function of V_F




Fig 9. Typical switching time as a function of I_c




Fig 10. Typical switching times as a function of R_G




Fig 11. Typical switching energy losses as a function of I_c




Fig 12. Typical switching energy losses as a function of R_G




Fig 13. Typical capacitance as a function of V_{CE}
($f=1\text{MHz}$, $V_{GE}=0\text{V}$)




Fig 14. Transient thermal impedance of IGBT



1600

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.95	16.00	16.05	0.627	0.62	



Date	Revision	Changes
2026-04-20	Rev 1.0	Preliminary Version
2026-06-25	Rev 1.1	Add thermal

PLEASE NOTE - Jiangsu JieJie Microelectronics Co., Ltd ("JJM") reserves the right to amend, correct, modify and enhance the product and/or this document at any time without prior notice. If you intend to purchase this product, please obtain the latest information available before placing your order. The sale of JJM products is governed by JJM's prevailing terms and conditions at the time of purchase and purchasers are solely responsible for the selection and use of the products with no liability on JJM's part to supply application assistance or customization. Purchase of JJM products does not grant the purchaser license, express or implied, to JJM's intellectual property. Any warranties provided with JJM products are null and void upon resale unless accompanied by the information set forth herein in its entirety. The JJM name and logo are registered trademarks of Jiangsu JieJie Microelectronics Co., Ltd. This document supersedes all previous versions. ©2026 JJM - All rights reserved